


Technical data sheet

Height compensation set (215-270 mm) for UZD250-3 with height 165–220 mm

Item number: 7410162



Height compensation set for underfloor boxes UZD250-3 with a construction height of 165 to 220 mm for construction stacking of the UZD to a height of 215-270 mm, consisting of four fall plates, four height adjustment screws and four rotary locks.



St Steel

FS Strip galvanized

Master data

Item number	7410162
Type	ASH250-3 265320
Description 1	Height construction set
Description 2	for screed height 265+55mm
Manufacturer	OBO
Material	Steel
Surface	Strip galvanized
Surface standard	DIN EN 10346
Smallest sales unit	1
Unit of quantity	Piece
Weight	127 kg
Weight unit	kg/100 pc.

Technical data sheet

Height compensation set (215-270 mm) for UZD250-3 with height 165–220 mm



Item number: 7410162



Dimensions



Dimension A	330 mm
Dimension B	130 mm
Dimension I	262 mm



Technical data

Version for	Square
Floor plate	no
Lowerable to be flush-floor	no
Seal installation option	no
Installation opening for on-floor tank	no
Decouplable	no
Screed height, max.	320 mm
Screed height, min.	265 mm
For pipe connection	no
Suitable for raised floor installation	no
Suitable for screed-flush closed underfloor ducts	no
Suitable for screed-covered underfloor ducts	yes
Suitable for cavity floor installation	no
Suitable for underfloor ducts	no
Trunking width, max.	250 mm
Trunking width, min.	190 mm
Height-adjustment range, max.	320 mm
Height-adjustment range, min.	265 mm